



## CERTIFICATION RECORD

The company named below has been authorized by CSA International to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

File No: 237865

Class No: 4228 01 MOTORS AND GENERATORS For Hazardous Locations

### SUBMITTOR

4736039 Ward Leonard Electric Company  
401 Watertown Rd  
Thomaston, CT 06787  
USA

### FACTORIES

4736039 Ward Leonard Electric Company  
401 Watertown Rd  
Thomaston, CT 06787  
USA

July 22, 2015 (Replaces: September 16,2014)

Class I, Div 2, Groups A, B, C, D; Temperature Coded T3:

Ex e IIC T3

- Squirrel cage induction motors, Type WL250060 for use with ABB Oy, Type ACS 800 07 0870/7 Variable Speed Drives, rated 575V ac, 600 hp max, 2670 lb-ft, 580 A; three phase, 2600 rpm max, Class H insulation, -40°C to + 55°C max ambient. Inverter Duty: 0 to 120 Hz (variable frequency).
- Squirrel cage induction motors, Type WL250040 for use with ABB Oy, Type ACS 800 07 0750/7 Variable Speed Drives, rated 575V ac, 450 hp max, 39 Hz, 350 A; three phase, 2400 rpm max, Class H insulation, 55 °C max ambient. Inverter Duty: 0 to 120 Hz (variable frequency).
- Squirrel cage induction motors, Type WL752115 for use with MI Electrical ACD 37 600 Variable Speed Drive, rated 575 V ac, 1200 hp max, 7890 lb-ft, three phase, 1800 rpm max, Class H insulation, up to 50 °C max ambient. Inverter Duty: 0 to 90 Hz (variable frequency).

Class I, Div 2, Groups A,B,C, D; Temperature Coded T3

- Squirrel cage induction motors, Type WL29BC160 rated 550V ac, 1600 hp max, 1590 amps, 9500 Lb-ft Torque, ; 3 Ph, 45Hz, 887 RPM, Class H insulation, -40 to +50 °C max ambient.
- Squirrel cage induction motors, Type WL29B180 rated 600V ac, 1800 hp max, 1610 amps, 9590 Lb-ftTorque; 3 Ph, 50Hz, 986 RPM, Class H insulation, -40 to +65°C max ambient.
- Squirrel cage induction motors, Type WL29B150 rated 550V ac, 1500 hp max, 1630 amps, 9985 Lb-ftTorque; 3 Ph, 40Hz, 790 RPM, Class H insulation, -40 to +40°C max ambient
- Squirrel cage induction motors, Type WL29B200 rated 600V ac, 2000 hp max, 1780 amps, 10,635 Lb-ftTorque; 3 Ph, 50Hz, 990 RPM, Class H insulation, -40 to +40°C max ambient.

Notes: 1) “Component certification only” are for use only as component parts of Certified equipment which provides for their proper use (e.g. such motors may have exposed live or moving parts which are required to be closed by the equipment in which they are intended to be used)

2) Motor to be supplied with blower assembly 3250 CFM of cooling air during continuous operation is not part of CSA certification

/sl